

# USB 24 V High Current Digital I/O Module - Isolated Model JI-4616

Jupiter Instruments

Ver 1.1

1/9/2012 Edition

## Electrical Specifications

Input/Output	
Inputs:	
Channel Count	8
Input Voltage	Range: -32 VDC to 32 VDC
	V <sub>IH</sub> high input: 3.0 V min
	V <sub>IL</sub> low input: 1.0 V max
Isolation*	500 VDC
Input Resistance	4.7K
Pulse Width	1.2mS min
ESD Protection	4000V Human-Body Model (A114-A)
Outputs:	
Channel Count	8
Output Type	Low-Side MOSFET Switch, Current-Sink
Switching Voltage	2 VDC min - 28 VDC max
Switching Current	2.0 A max per channel
Voltage Clamp	30 V nominal
Isolation*	500 VDC
Protection Function	Short Circuit & Thermal Shut-Down
ESD Protection	2000V Human-Body Model (A114-A)
Power	
USB	
Input voltage	4.7 to 5.25 VDC when configured
Current Consumption	Active State: 135 mA max
PC Interface	
Communication	USB 2.0 Full Speed
Connector	Standard type B socket

\* Input channels are comprised of 2 banks of 4 inputs and output channels are comprised of 2 banks of 4 inputs. A ground is provided for each bank. Isolation is measured between bank-to-bank and bank-to-ground. See JI-4040 block for isolation arrangement.

## Mechanical and Environmental Specifications

<b>Mechanical</b>	
Dimensions	Board only: 3.9" x 0.5" x 4.7" (WxHxL)
	Enclosure: 4.1" x 1.1" x 5.5" (WxHxL)
Weight	Board only: 0.1 lbs
	Enclosure: 0.9 lbs
<b>Environmental</b>	
Operating Temperature	Board only: 0C to 70C
	Enclosure: 0C to 60C
Storage Temperature	-40C to 70C